



James Briggs Ltd

Salmon Fields, Royton, Oldham OL2 6HZ UK Tel: 0161 627 0101 Fax: 0161 627 0971 www.jamesbriggs.co.uk

TECHNICAL DATA SHEET

CARB CLEAN XUK303

1. Introduction

A powerful, blended solvent degreaser, designed primarily to clean deposits from carburettors, and induction system components.

2. Where to Use

For the removal of oil, grease and gum deposits from metallic components utilized in carburettors and fuel injection systems, in particular carburettor bodies, air control valves, throttle bodies, air intake butterfly valves etc.

3. Where not to use

- On painted or decorative surfaces.
- On natural and synthetic plastics or rubbers.

4. Benefits

- Dissolves all conventional automotive oil and grease deposits.
- Rapidly softens and removes fuel deposits.
- Helps restore engine performance.
- Safe for use in conjunction with oxygen sensors and catalytic converters.

5. Physical Properties [Carb Clean base except where stated]

Appearance A fast drying red liquid with a strong aromatic odour.

pH Not applicable Specific Gravity 0.685 - 0.705

Viscosity Thin free flowing liquid

Non Volatiles % m/m < 0.05Active Content % m/m, as supplied 65 - 75

Flammability, as supplied Extremely flammable, flash point below -20°C. Composition Data, as supplied A blend of aromatic and aliphatic hydrocarbons in

butane/isobutane/propane propellant.
Service temperature Designed for use at ambient temperatures

6. Application

Set engine to fast idle speed and spray directly into the throat and butterfly assembly. For all other applications spray apply liberally directly from the surface from a distance of 20 - 30 cm. Saturate the surface, and collect run-off with an absorbent cloth or towel and collect contaminated fluid in a tray.

For induction systems, switch the engine off, and disconnect the induction tube. Attach the extension tube and spray into the body until clean. Replace induction tube.

7. Availability

400ml. aerosols

B076508, August 2017