

## SAFETY DATA SHEET XUK989 TRUCK BED LINER 400ML

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name XUK989 TRUCK BED LINER 400ML  
Product No. XUK989

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Supplier James Briggs Limited  
4 Howarth Court,  
Gateway Crescent, Chadderton,  
Oldham, Lancashire  
OL9 9XB  
England  
0161 627 0101  
sds@jamesbriggs.co.uk

#### 1.4. Emergency telephone number

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Flam. Aerosol 1 - H222  
Human health EUH066; Eye Irrit. 2 - H319; STOT SE 3 - H336  
Environment Aquatic Chronic 3 - H412

Classification (1999/45/EEC) Xi; R36. F+; R12. R52/53, R66, R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### 2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word Danger

Hazard Statements

H222	Extremely flammable aerosol.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P313	Get medical advice/attention.
P501	Dispose of contents/container to ...

Supplementary Precautionary Statements

P273	Avoid release to the environment.
------	-----------------------------------

## XUK989 TRUCK BED LINER 400ML

P261	Avoid breathing vapour/spray.
P264	Wash contaminated skin thoroughly after handling.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337	If eye irritation persists:
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

### Supplemental label information

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains COBALT BIS(2-ETHYLHEXANOATE),ETHYL METHYL KETOXIME. May produce an allergic reaction.

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

<p>ACETONE <span style="float: right;">10-30%</span></p> <p>CAS-No.: 67-64-1 <span style="margin-left: 150px;">EC No.: 200-662-2</span></p>		
<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;"> <p>Classification (EC 1272/2008)</p> <p>Flam. Liq. 2 - H225</p> <p>EUH066</p> <p>Eye Irrit. 2 - H319</p> <p>STOT SE 3 - H336</p> </td> <td style="width: 50%;"> <p>Classification (67/548/EEC)</p> <p>F;R11</p> <p>Xi;R36</p> <p>R66</p> <p>R67</p> </td> </tr> </table>	<p>Classification (EC 1272/2008)</p> <p>Flam. Liq. 2 - H225</p> <p>EUH066</p> <p>Eye Irrit. 2 - H319</p> <p>STOT SE 3 - H336</p>	<p>Classification (67/548/EEC)</p> <p>F;R11</p> <p>Xi;R36</p> <p>R66</p> <p>R67</p>
<p>Classification (EC 1272/2008)</p> <p>Flam. Liq. 2 - H225</p> <p>EUH066</p> <p>Eye Irrit. 2 - H319</p> <p>STOT SE 3 - H336</p>	<p>Classification (67/548/EEC)</p> <p>F;R11</p> <p>Xi;R36</p> <p>R66</p> <p>R67</p>	
<p>BUTANE <span style="float: right;">5-10%</span></p> <p>CAS-No.: 106-97-8 <span style="margin-left: 150px;">EC No.: 203-448-7</span></p>		
<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;"> <p>Classification (EC 1272/2008)</p> <p>Flam. Gas 1 - H220</p> </td> <td style="width: 50%;"> <p>Classification (67/548/EEC)</p> <p>F+;R12</p> </td> </tr> </table>	<p>Classification (EC 1272/2008)</p> <p>Flam. Gas 1 - H220</p>	<p>Classification (67/548/EEC)</p> <p>F+;R12</p>
<p>Classification (EC 1272/2008)</p> <p>Flam. Gas 1 - H220</p>	<p>Classification (67/548/EEC)</p> <p>F+;R12</p>	
<p>COBALT BIS(2-ETHYLHEXANOATE) <span style="float: right;">&lt; 1%</span></p> <p>CAS-No.: 136-52-7 <span style="margin-left: 150px;">EC No.: 205-250-6</span></p>		
<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;"> <p>Classification (EC 1272/2008)</p> <p>Not classified.</p> </td> <td style="width: 50%;"> <p>Classification (67/548/EEC)</p> <p>Xn;R22.</p> <p>Xi;R38.</p> <p>R43.</p> </td> </tr> </table>	<p>Classification (EC 1272/2008)</p> <p>Not classified.</p>	<p>Classification (67/548/EEC)</p> <p>Xn;R22.</p> <p>Xi;R38.</p> <p>R43.</p>
<p>Classification (EC 1272/2008)</p> <p>Not classified.</p>	<p>Classification (67/548/EEC)</p> <p>Xn;R22.</p> <p>Xi;R38.</p> <p>R43.</p>	
<p>ETHYL METHYL KETOXIME <span style="float: right;">&lt; 1%</span></p> <p>CAS-No.: 96-29-7 <span style="margin-left: 150px;">EC No.: 202-496-6</span></p>		
<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;"> <p>Classification (EC 1272/2008)</p> <p>Acute Tox. 4 - H312</p> <p>Eye Dam. 1 - H318</p> <p>Skin Sens. 1 - H317</p> <p>Carc. 2 - H351</p> </td> <td style="width: 50%;"> <p>Classification (67/548/EEC)</p> <p>Carc. Cat. 3;R40</p> <p>Xn;R21</p> <p>R43</p> <p>Xi;R41</p> </td> </tr> </table>	<p>Classification (EC 1272/2008)</p> <p>Acute Tox. 4 - H312</p> <p>Eye Dam. 1 - H318</p> <p>Skin Sens. 1 - H317</p> <p>Carc. 2 - H351</p>	<p>Classification (67/548/EEC)</p> <p>Carc. Cat. 3;R40</p> <p>Xn;R21</p> <p>R43</p> <p>Xi;R41</p>
<p>Classification (EC 1272/2008)</p> <p>Acute Tox. 4 - H312</p> <p>Eye Dam. 1 - H318</p> <p>Skin Sens. 1 - H317</p> <p>Carc. 2 - H351</p>	<p>Classification (67/548/EEC)</p> <p>Carc. Cat. 3;R40</p> <p>Xn;R21</p> <p>R43</p> <p>Xi;R41</p>	

## XUK989 TRUCK BED LINER 400ML

ISOBUTANE		1-5%
CAS-No.: 75-28-5	EC No.: 200-857-2	
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12	
NAPHTHA(PETROLEUM),HYDRODESULPHURISED HEAVY		10-30%
CAS-No.: 64742-82-1	EC No.:	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Xn;R65. N;R51/53. R10,R66,R67.	
PROPANE		10-30%
CAS-No.: 74-98-6	EC No.: 200-827-9	
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12	
XYLENE		1-5%
CAS-No.: 1330-20-7	EC No.: 215-535-7	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412	Classification (67/548/EEC) R10 Xn;R20/21 Xi;R38	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures

##### General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

##### Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

##### Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

##### Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

##### Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

#### 4.2. Most important symptoms and effects, both acute and delayed

# XUK989 TRUCK BED LINER 400ML

## 4.3. Indication of any immediate medical attention and special treatment needed

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1. Extinguishing media

Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

#### 5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire.

#### 5.3. Advice for firefighters

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.2. Environmental precautions

#### 6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

#### 6.4. Reference to other sections

### SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

#### 7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

#### 7.3. Specific end use(s)

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ACETONE	WEL	500 ppm	1210 mg/m <sup>3</sup>	1500 ppm	3620 mg/m <sup>3</sup>	
BUTANE	WEL	600 ppm	1450 mg/m <sup>3</sup>	750 ppm	1810 mg/m <sup>3</sup>	
PROPANE		Asphyxiating	Asphyxiating.	Asphyxiating	Asphyxiating.	
XYLENE	WEL	50 ppm(Sk)	220 mg/m <sup>3</sup> (Sk)	100 ppm(Sk)	441 mg/m <sup>3</sup> (Sk)	

WEL = Workplace Exposure Limit.

#### 8.2. Exposure controls

Protective equipment

# XUK989 TRUCK BED LINER 400ML



## Engineering measures

Provide adequate general and local exhaust ventilation.

## Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

## Hand protection

Use protective gloves.

## Eye protection

Use approved safety goggles or face shield.

## Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

## Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Typical
Odour	Characteristic.
Flammability Limit - Lower(%)	0.8
Flammability Limit - Upper(%)	9.0

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Irritating to respiratory system.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

# XUK989 TRUCK BED LINER 400ML

## Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause allergic contact eczema. May cause sensitisation by skin contact. Irritating to skin.

## Eye contact

Irritating to eyes. May cause chemical eye burns.

## Route of entry

Inhalation. Skin and/or eye contact.

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

Dangerous for the environment if discharged into watercourses.

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. UN number

UN No. (ADR/RID/ADN)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

### 14.2. UN proper shipping name

Proper Shipping Name	AEROSOLS
----------------------	----------

### 14.3. Transport hazard class(es)

ADR/RID/ADN Class	2
ADR/RID/ADN Class	Class 2: Gases
ADR Label No.	2.1
IMDG Class	2.1
ICAO Class/Division	2.1
Transport Labels	



# XUK989 TRUCK BED LINER 400ML

## **14.4. Packing group**

ADR/RID/ADN Packing group	Not Applicable
IMDG Packing group	Not Applicable
ICAO Packing group	Not Applicable

## **14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant

No.

## **14.6. Special precautions for user**

EMS F-D, S-U

## **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

### **SECTION 15: REGULATORY INFORMATION**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Uk Regulatory References

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

Statutory Instruments

The Control of Substances Hazardous to Health Regulations 2002.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

#### **15.2. Chemical Safety Assessment**

### **SECTION 16: OTHER INFORMATION**

Revision Date 19/05/2016

Revision 5

Supersedes date 29/04/2014

Risk Phrases In Full

R12	Extremely flammable.
R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R22	Harmful if swallowed.
R21	Harmful in contact with skin.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable
R36	Irritating to eyes.
R38	Irritating to skin.
R40	Limited evidence of a carcinogenic effect.
R43	May cause sensitisation by skin contact.
R66	Repeated exposure may cause skin dryness or cracking.
R41	Risk of serious damage to eyes.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

## XUK989 TRUCK BED LINER 400ML

### Hazard Statements In Full

H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H222	Extremely flammable aerosol.
H220	Extremely flammable gas.
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H312	Harmful in contact with skin.
H412	Harmful to aquatic life with long lasting effects.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs <<Organs>> through prolonged or repeated exposure.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.
EUH066	Repeated exposure may cause skin dryness or cracking.
H351	Suspected of causing cancer.