



James Briggs Ltd
Salmon Fields, Royton, Oldham OL2 6HZ UK
Tel: 0161 627 0101 Fax: 0161 627 0971
www.jamesbriggs.co.uk

TECHNICAL DATA SHEET

MAINTENANCE SPRAY UK808 / UK976

1. Introduction

A multi purpose lubricant with cleaning, lubricating, dewatering, penetrating and corrosion inhibition properties.

2. Where to use

On all ferrous metals, as a general purpose lubricant specifically designed to release seized and corroded components, as a general purpose lubricant, a dewatering fluid or as a temporary anti-corrosive coating.

3. Where not to use

- No restrictions

4. Benefits

- Excellent lubrication properties.
- All Angle Spray (*)
- Moisture displacement.
- Moisture repellency.
- Cleans - removes oily deposits, greases, adhesive label residues etc
- Formation of a temporary anti-corrosive coating.
- Ability to penetrate rust and corrosion deposits.

4. Physical properties. [Maintenance Spray base except where stated]

Appearance	Clear/turbid brown liquid.
pH	Not applicable
Specific Gravity	0.785 – 0.815
Viscosity	Low viscosity, free flowing liquid
Non-Volatiles % m/m	10 - 20
Active Content % m/m, as supplied	10 - 20
Flammability, as supplied	Extremely flammable, flash point below -20°C.
Composition Data, as supplied	A solution of a mineral oil, modified grease, water displacing additives, PTFE, fragrance and wetting agents in a blend of hydrocarbon solvents, in a butane/isobutane/propane propellant.
Service Temperature	Designed for use at ambient temperatures.

6. Application Details

Shake thoroughly before use. Spray directly onto the component or surface, from a distance of 15 to 25cm, and allow to penetrate or form a film depending upon requirement.

7. Availability

400ml, 600ml(*). Aerosols.

B05005A, RJB August 2017