



TECHNICAL DATA SHEET

James Briggs Ltd

Salmon Fields, Royton, Oldham OL2 6HZ UK Tel: 0161 627 0101 Fax: 0161 627 0971 www.jamesbriggs.co.uk PANEL PREP DEGREASER XUK996

1. Introduction

A fast acting solvent blend designed for degreasing metal and paintwork prior to coating.

2. Where to Use

On any metallic substrate, for the removal of newly deposited, aged or oxidised greases, oils, bitumen and tar stains, waxes, silicones etc. This product is also suitable for spot removal use on concretes, and on many plastics and painted surfaces subject to successful assessment on an inconspicuous area.

3. Where not to use

Over asphalt, soft plastics and some painted surfaces.

4. Benefits

- Dissolves all conventional automotive oils and greases.
- Easy to use spray action
- Fast drying formulation
- Use on metals, plastics and glass
- Smooth professional finish

5. Physical Properties [Degreaser Base except where stated]

Appearance A colourless liquid with a hydrocarbon solvent odour.

pH Not applicable Specific Gravity 0.770 – 0.800

Viscosity Thin free flowing liquid

Non Volatiles % m/m 0% Active Content % m/m, as supplied 75%

Flammability, as supplied Extremely flammable, flash point below -20°C.

Composition data, as supplied A blend of xylene, aliphatic and alcoholic solvent in a

butane/isobutane/propane propellant.

Service temperature Designed for use at ambient temperatures.

6. Application

Shake can thoroughly before use. Spray liberally on the designated area. Allow to remain in contact with the surface for a few moments to penetrate and solublise contamination before wiping over with a clean dry lint free cloth. Brushing or other forms of agitation will assist in effective solublisation of stubborn deposits.

Always dispose of contaminated materials in a sealable metal bin to prevent fire risk.

7. Availability

400ml aerosols

RJB August 2017