

SAFETY DATA SHEET SILVER WHEEL UK402

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name SILVER WHEEL UK402
Product No. XUK402

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Sealer.

1.3. Details of the supplier of the safety data sheet

Supplier James Briggs Limited
4, Howarth Court,
Gateway Crescent, Chadderton,
Oldham, Lancashire,
OL9 9XB,
England
0161 627 0101
sds@jamesbriggs.co.uk

1.4. Emergency telephone number

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

| | |
|-------------------------------|--------------------------------------------------------------------|
| Physical and Chemical Hazards | Flam. Aerosol 1 - H222 |
| Human health | EUH066;Acute Tox. 4 - H312;Acute Tox. 4 - H332;Eye Irrit. 2 - H319 |
| Environment | Aquatic Chronic 3 - H412 |

Classification (1999/45/EEC)

Xn;R20/21. Xi;R36. F+;R12. R52/53, R66.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

2.2. Label elements

Contains XYLENE

Label In Accordance With (EC) No. 1272/2008



Signal Word Danger

Hazard Statements

| | |
|------|----------------------------------------------------|
| H222 | Extremely flammable aerosol. |
| H312 | Harmful in contact with skin. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H412 | Harmful to aquatic life with long lasting effects. |

Precautionary Statements

| | |
|----------|----------------------------------------------------------------------------|
| P102 | Keep out of reach of children. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P261 | Avoid breathing vapour/spray. |
| P337+313 | If eye irritation persists: Get medical advice/attention. |

SILVER WHEEL UK402

| | | |
|----------------------------------------|--------------|----------------------------------------------------------------------------------------------------------------------------------|
| | P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses. if present and easy to do. Continue rinsing. |
| | P501 | Dispose of contents/container in accordance with local regulations. |
| Supplementary Precautionary Statements | P211 | Do not spray on an open flame or other ignition source. |
| | P251 | Pressurized container: Do not pierce or burn, even after use. |
| | P264 | Wash contaminated skin thoroughly after handling. |
| | P302+352 | IF ON SKIN: Wash with plenty of soap and water. |
| | P304+340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| | P312 | Call a POISON CENTER or doctor/physician if you feel unwell. |
| | P410+412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. |
| Supplemental label information | | |
| | EUH066 | Repeated exposure may cause skin dryness or cracking. |
| | | H229 Pressurised container: May burst if heated |

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

| | |
|---------------------------------------------------------------------------------------|-------------------------------------------------------|
| 1-METHOXY-2-PROPANOL | 1-5% |
| CAS-No.: 107-98-2 | EC No.: 203-539-1 |
| Classification (EC 1272/2008) Flam. Liq. 3 - H226 | Classification (67/548/EEC) R10 |
| ACETONE | 30-60% |
| CAS-No.: 67-64-1 | EC No.: 200-662-2 |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 Eye Irrit. 2 - H319 | Classification (67/548/EEC) F;R11 Xi;R36 R66 |
| BUTANE | 10-30% |
| CAS-No.: 106-97-8 | EC No.: 203-448-7 |
| Classification (EC 1272/2008) Flam. Gas 1 - H220 | Classification (67/548/EEC) F+R12 |
| ISOBUTANE | 5-10% |
| CAS-No.: 75-28-5 | EC No.: 200-857-2 |
| Classification (EC 1272/2008) Flam. Gas 1 - H220 | Classification (67/548/EEC) F+R12 |

SILVER WHEEL UK402

| | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|
| ISODECYLOXYPROPYLAMINE ACETATE < 1% | |
| CAS-No.: 28701-67-9 | EC No.: |
| Classification (EC 1272/2008) Acute Tox. 4 - H302 Skin Corr. 1B - H314 Aquatic Acute 1 - H400 | Classification (67/548/EEC) Xn;R22. C;R34. ----- |
| PROPANE 10-30% | |
| CAS-No.: 74-98-6 | EC No.: 200-827-9 |
| Classification (EC 1272/2008) Flam. Gas 1 - H220 | Classification (67/548/EEC) F+R12 |
| STODDARD SOLVENT 1-5% | |
| CAS-No.: 8052-41-3 | EC No.: 232-489-3 |
| Classification (EC 1272/2008) Flam. Liq. 3 - H226 Asp. Tox. 1 - H304 | Classification (67/548/EEC) Xn;R65. N;R51/53. |
| XYLENE 10-30% | |
| CAS-No.: 1330-20-7 | EC No.: 215-535-7 |
| Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 | Classification (67/548/EEC) R10 Xn;R20/21 ----- |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues

Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

SILVER WHEEL UK402

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

| Name | STD | TWA - 8 Hrs | | STEL - 15 Min | | Notes |
|----------------------|-----|----------------|------------------|----------------|------------------|-------|
| 1-METHOXY-2-PROPANOL | WEL | 100 ppm(Sk) | 375 mg/m3(Sk) | 150 ppm(Sk) | 560 mg/m3(Sk) | |
| ACETONE | WEL | 500 ppm | 1210 mg/m3 | 1500 ppm | 3620 mg/m3 | |
| BUTANE | WEL | 600 ppm | 1450 mg/m3 | 750 ppm | 1810 mg/m3 | |
| PROPANE | | Asphyxiating | Asphyxiating. | Asphyxiating | Asphyxiating. | |
| XYLENE | WEL | 50 ppm(Sk) | 220 mg/m3(Sk) | 100 ppm(Sk) | 441 mg/m3(Sk) | |

SILVER WHEEL UK402

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Use eye protection.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| | |
|-------------------------------|--------------------|
| Appearance | Aerosol. |
| Colour | Silver. |
| Odour | Characteristic. |
| Solubility | Insoluble in water |
| Flammability Limit - Lower(%) | 0.8 |
| Flammability Limit - Upper(%) | 13.0 |

9.2. Other information

| | |
|---------------------------------|-------------|
| Volatile Organic Compound (VOC) | 656 g/litre |
|---------------------------------|-------------|

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

SILVER WHEEL UK402

Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Harmful by inhalation. Irritating to respiratory system.

Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

Skin contact

Harmful in contact with skin. Irritating to skin. Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin and eczema.

Eye contact

Irritating to eyes. May cause chemical eye burns.

Route of entry

Inhalation. Skin and/or eye contact.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

| | |
|----------------------|------|
| UN No. (ADR/RID/ADN) | 1950 |
| UN No. (IMDG) | 1950 |
| UN No. (ICAO) | 1950 |

14.2. UN proper shipping name

| | |
|----------------------|----------|
| Proper Shipping Name | AEROSOLS |
|----------------------|----------|

14.3. Transport hazard class(es)

| | |
|---------------------|----------------|
| ADR/RID/ADN Class | 2 |
| ADR/RID/ADN Class | Class 2: Gases |
| ADR Label No. | 2.1 |
| IMDG Class | 2.1 |
| ICAO Class/Division | 2.1 |
| Transport Labels | |

**14.4. Packing group**

| | |
|---------------------------|-----|
| ADR/RID/ADN Packing group | N/A |
| IMDG Packing group | N/A |
| ICAO Packing group | N/A |

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant
No.

14.6. Special precautions for user

| | |
|-------------------------|----------|
| EMS | F-D, S-U |
| Tunnel Restriction Code | (D) |

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Uk Regulatory References

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

Statutory Instruments

Control of Substances Hazardous to Health.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

| | |
|-----------------|------------|
| Revision Date | 07/01/2016 |
| Revision | 20 |
| Supersedes date | 14/11/2014 |

SILVER WHEEL UK402

Risk Phrases In Full

| | |
|--------|--------------------------------------------------------------------------------------------------|
| R34 | Causes burns. |
| R12 | Extremely flammable. |
| R10 | Flammable. |
| R20/21 | Harmful by inhalation and in contact with skin. |
| R22 | Harmful if swallowed. |
| R52/53 | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R65 | Harmful: may cause lung damage if swallowed. |
| R11 | Highly flammable |
| R36 | Irritating to eyes. |
| R38 | Irritating to skin. |
| R66 | Repeated exposure may cause skin dryness or cracking. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R67 | Vapours may cause drowsiness and dizziness. |
| R50/53 | Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |

Hazard Statements In Full

| | |
|--------|-------------------------------------------------------------------------------|
| H319 | Causes serious eye irritation. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H222 | Extremely flammable aerosol. |
| H220 | Extremely flammable gas. |
| H226 | Flammable liquid and vapour. |
| H332 | Harmful if inhaled. |
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin. |
| H412 | Harmful to aquatic life with long lasting effects. |
| H225 | Highly flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H373 | May cause damage to organs <<Organs>> through prolonged or repeated exposure. |
| H336 | May cause drowsiness or dizziness. |
| H335 | May cause respiratory irritation. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H400 | Very toxic to aquatic life. |

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his